RECEIVEYAMH 54183

AUG 2 9 2005 STATE OF OREGON

WATER SUPPLY WELL REPORT (as required by ORS 537.765)

WATER RESOURCES DEFI

WELL I.D. # L	73646		
---------------	-------	--	--

START CARD # 148531

nstructions for completing this report are on the last page of this form.				
1) LAND OWNER Well Number nw Name Maralynn Abrams	(9) LOCATION OF WELL (legal description) County Yamhill Tax Lot 100 Lot			
Address 12477 Baker Creek Rd.	Tax Lot 100 Lot			
	Township 4 S Range 5 W	WM		
City McMinnville State Or Zip 97128	Section 13 NE 1/4 SE	1/4		
2) TYPE OF WORK New Well Deepening Alteration (repair/recondition) Abandonment Conversion	Lat " or (degree to leave t			
	Long or (degrees or decimal)			
3) DRILL METHOD Rotary Air Rotary Mud Cable Auger Cable Mud Other	Street Address of Well (or nearest address) 12475 Baker Creek Rd.			
4) PROPOSED USE Domestic Community Industrial Irrigation	(10) STATIC WATER LEVEL 105 ft. below land surface. Date 8-11-05			
☐ Thermal ☐ Injection ☐ Livestock ☐ Other	ft. below land surface. Date			
5) BORE HOLE CONSTRUCTION Special Construction: Yes No Depth of Completed Well 218 ft. Explosives used: Yes No Type Amount	Artesian pressurelb. per square inch Date (11) WATER BEARING ZONES			
	Depth at which water was first found 26' From To Estimated Flow Rate	SWL		
BORE HOLE SEAL Diameter From To Material From To Sacks or Pounds		105'		
10" 0 52 bentonite 0 50 28 sacks	120 1.00	105'		
8" 52 138				
5.5" 138 218	26 27 Trace			
How was seal placed: Method ABCDDE Other poured dry and hydrated (12) WELL LOG Ground Elevation				
Backfill placed from 50 ft. to 52 ft. Material bentonite	Material From To	SWL		
Gravel placed fromft. toft. Size of gravel				
	Clay, orange, sticky 5 17 Clay, yellow, sticky 17 21			
(6) CASING/LINER	Clay, grey, sandy 21 27			
Diameter From To Gauge Steel Plastic Welded Threaded	Clay, grey, sandy Clay, orange, sticky 27 41			
Casing: 6" +28" 138' 250	Basalt, weathered 41 68			
Liner: none	Basalt, black/brown, fractured 68 72			
	Basalt, black, fractured 72 105			
Liner: none	Basalt, black/brown, fractured 105 118			
	Clay, yellow, sandy 118 122			
	Conglomerate, grey, grainy, fract 122 163	105'		
Drive Shoe used Inside Outside None	Conglomerate, grey, grainy, hard 163 178	105'		
Final location of shoe(s) 138'	Claystone, grey, soft 178 181	105'		
TO DEDUCE A TRANSPORTENCE	Claystone, grey, med 181 218	105'		
(7) PERFORATIONS/SCREENS Perforations Method none	Dickerson Well Drilling, Inc.			
	Ph# (503) 623-2664			
Screens Type Material	Date Started <u>8-9-05</u> Completed <u>8-11-05</u>			
From To Slot Number Diameter Tele/pipe Casing Liner Size Size	(unbonded) Water Well Constructor Certification I certify that the work I performed on the construction, deepening, alteration, or abandonment of this well is in compliance with Oregon water supply well construction standards. Materials used and information reported above are true to the best of my knowledge and belief.			
	WWC Number Date			
(8) WELL TESTS: Minimum testing time is 1 hour ☐ Pump ☐ Bailer ☑ Air ☐ Flowing Artesian	Signed			
Yield gal/min Drawdown Drill stem at Time 50+ 218' 1hr	(bonded) Water Well Constructor Certification I accept responsibility for the construction, deepening, alteration, or abandonment work performed on this well during the construction dates reported above. All work performed during this time is in compliance with Oregon water			
Temperature of water 54 Depth Artesian Flow Found	supply well construction standards. This report is true to the best of	шу кложиеаде		
Was a water analysis done? Yes By whom	and belief.			
Was a water analysis done? Yes By whom Did any strata contain water not suitable for intended use? Too little	WWC Number 1571 Date 8-23-05			
·	1			
☐ Salty ☐ Muddy ☐ Odor ☐ Colored ☐ Other Depth of strata: 218' (cond 176us)	Signed William A. Blair			