STATE OF OREGON WATER SUPPLY WELL REPORT

(as required by ORS 537.765)

Mack Drilling Company, Inc. PO Box 12067 Salem, OR 97309

WELL I.D. # L 79266 page one of two

START CARD # 180504

Instructions for completing this report are on the last page of this form.		
(1) LAND OWNER Well Number 79266 Name Adelsheim Vineyard, LLC	(9) LOCATION OF WELL (legal description) County Yamhill	
Address P. O. Box 909	Tax Lot 3200 Lot	
City Newberg State OR Zip 97132	Township 3 S Range 3 W Section 3 SW 1/4 NW	WM
	Section 3 SW 1/4 NW	1/4
(2) TYPE OF WORK	Lat or (degrees of Long or (degrees or or	or decimal)
(3) DRILL METHOD		
Z Rotary Air	Street Address of Well (or nearest address) 16800 NE Calkins Lane, Newberg, OR 97132	
(4) PROPOSED USE	(10) STATIC WATER LEVEL	
☐ Domestic ☐ Community ☐ Industrial ☑ Irrigation	ft. below land surface. Date 10-18-05	
☐ Thermal ☐ Injection ☐ Livestock ☐ Other	ft. below land surface. Date	
	Artesian pressurelb. per square inch	
(5) BORE HOLE CONSTRUCTION Special Construction: ☐ Yes ☑ No Depth of Completed Well 164 ft.		
Depth of Completed Well 164 ft. Explosives used: Yes No Type Amount Amount	(11) WATER BEARING ZONES Denth at which water was first found 40	
BORE HOLE SEAL Diameter From To Material From To Sacks or Pounds	From To Estimated Flow Rate 40 60 10 19	SWL
10 0 30 Bentonite 0 15 8 sacks	85 88 3 19	
6 30 160 Cement 15 30 4 sks w/bent	112 117 2 19	
How was seal placed: Method A B C D E	(12) WELL LOG Ground Elevation	
Other Poured & Probed	Material From To	SWL
Backfill placed fromft. toft. Material		5 W E
Gravel placed fromft. toft. Size of gravel		
(6) CASING/LINER		
Diameter From To Gauge Steel Plastic Welded Threaded		
Casing: 6 +1 39 .250		
Casing: 6 +1 39 .250		
Liner: 4 -04 164 160	RECEIVED	
	- INCOLIVED	
Drive Shoe used 🔲 Inside 🗾 Outside 🔲 None	007	
Final location of shoe(s) 39	OCT 3 1 2005	
	WATER RESQUECES DEF	
(7) PERFORATIONS/SCREENS ✓ Perforations Method Electric Saw	SALEM. OREGON	· · · · · · · · · · · · · · · · · · ·
✓ Perforations Method Electric Saw Screens Type Slots Material PVC		
	Date Started 10-18-05 Completed 10-18-05	
From To Slot Number Diameter Tele/pipe Casing Liner Size size	(unbonded) Water Well Constructor Certification	
	I certify that the work I performed on the construction, deepening, a	
64 164 1/8 60 6"	abandonment of this well is in compliance with Oregon water supply we construction standards. Materials used and information reported above	ill meteriete
	the best of my knowledge and belief	
		-
	WWC Number 1394 Date / 10 - 21 - 03	
(8) WELL TESTS: Minimum testing time is 1 hour	1 Sur / / / lash	
Pump Bailer Air Flowing Artesian	Signed Man (Muy)	
Yield gal/min Drawdown Drill stem at Time	(bonded) Water Well Constructor Certification	
15 160 1 HR	Faccept responsibility for the construction, deepening, alteration, or abandonment work performed on this well during the construction dates	
	above. All work performed during this time is in compliance with Oreg	
	supply well construction standards. This report is true to the best of my	
Temperature of water 52 Depth Artesian Flow Found	and haliaf	
Was a water analysis done? Yes By whom	WWC Number 1394 / Date 10 -21-05	_ ,
Did any strata contain water not suitable for intended use?	WWC Number 1394 Date / 0 27	
Salty Muddy Odor Colored Other	Signed upone L. Wark	
Depth of strata:	OI gillot	



Mack Drilling Company, Inc.

Domestic ◆ Commercial ◆ Environmental ◆ Geotechnical Drilling & Well Services

(1) OWNER: ADELSHEIM VINEYARDS, LLC	Well Number:	79266	
,	Start Card #	180504	
P.O. BOX 909	Site		
Address:	16800 NE Calkins L	N, Newberg	

NEWBERG, OR 97132 City:

Address:

	Page two of two		wo
12) WELL LOG:			
Material	From	То	SWL
******continued from page one*******			
Clay br some rusty, some green	0	14	
Siltstone grey soft to med-hard	14	21	
Siltstone grey hard w/Frx's	21	26	
Siltstone grey med-hard	26	43	
Claystone light & dark grey seamy	43	53	
Claystone br & green sandy med-hard	53	61	
Claystone dark br seams med-hard	61	65	
Claystone grey-br med-hard	65	68	
Siltstone dark grey hard	68	85	
Claystone blk	85	88	
Siltstone dark grey med-hard	88	91	
Sandstone white Frx hard	91	97	
Siltstone grey & green hard some sandy	97	102	
Siltstone dark grey hard	102	105	
Siltstone light & dark grey hard	105	108	
Siltstone dark grey	108	112	
Siltstone dark grey & br Frx	112	117	
Siltstone grey hard	117	120	
Siltstone multi greys & purple	120	128	
Siltstone dark grey	128	147	
Siltstone light & dark grey	147	164	
			REC
			OCT 3
	•	5.0 4.0	TER RESC