

NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

RECEIVED

APR 2 1969

STATE OF OREGON WATER WELL REPORT

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

STATE OF OREGON (Please type or print)

G-4830

State Well No. 4/4W-1000

State Permit No.

YAMHILL 5646

(1) OWNER:

Name Wallace Aebi Address Rte. 2 Box 184, McMinnville, Ore.

(11) LOCATION OF WELL:

County Yamhill Driller's well number NE 1/4 NE 1/4 Section 10 T. 4S R. 4W W.M.

(2) TYPE OF WORK (check):

New Well [X] Deepening [ ] Reconditioning [ ] Abandon [ ]

If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary [X] Driven [ ] Cable [ ] Jetted [ ] Dug [ ] Bored [ ]

(4) PROPOSED USE (check):

Domestic [X] Industrial [ ] Municipal [ ] Irrigation [ ] Test Well [X] Other [ ]

CASING INSTALLED:

6" Diam. from 0 ft. to 67 ft. Gage 250

PERFORATIONS:

Perforated? [X] Yes [ ] No. Type of perforator used Torch Size of perforations 1/4 in. by 12 in. 90 perforations from 49 ft. to 67 ft.

(7) SCREENS:

Well screen installed? [ ] Yes [X] No Manufacturer's Name Type Model No. Diam. Slot size Set from ft. to ft.

(8) WATER LEVEL: Completed well.

Static level ft. below land surface Date Artesian pressure 2 lbs. per square inch Date 3-1-69

(9) WELL TESTS:

Drawdown is amount water level is lowered below static level Was a pump test made? [ ] Yes [X] No Yield: gal./min. with ft. drawdown after hrs. Comp. test 100 gal./min. with 60 ft. drawdown after 3 hrs. Artesian flow 10 g.p.m. Date 3-1-69 Temperature of water 54.5 Was a chemical analysis made? [ ] Yes [X] No

(10) CONSTRUCTION:

Bentonite Packer Well seal—Material used Cement Grout Depth of seal 18 ft. Diameter of well bore to bottom of seal 12 in. Were any loose strata cemented off? [ ] Yes [X] No Depth Was a drive shoe used? [ ] Yes [X] No Did any strata contain unusable water? [ ] Yes [X] No Type of water? depth of strata Method of sealing strata off Was well gravel packed? [X] Yes [ ] No Size of gravel: 3/4 in. Gravel placed from 18 ft. to 67 ft.

(12) WELL LOG:

Diameter of well below casing 0 Depth drilled 67 ft. Depth of completed well 67 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level as drilling proceeds. Note drilling rates.

Table with columns: MATERIAL, From, To, SWL. Rows include Topsoil, Brown Clay, Fine Black sand, Sandy Yellow Clay, Black Sand with wood, Fine to Me.d. Gravel, Sandy Blue Clay.

Work started Feb. 26 19 69 Completed Mar. 1 19 69

Date well drilling machine moved off of well Mar. 1 19 69

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] James H. Wilcox (Drilling Machine Operator) Date Mar. 19, 19 69

Drilling Machine Operator's License No. 172

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

NAME Wilcox Drilling & Pump Co. (Person, firm or corporation) (Type or print)

Address P. O. Box 569, McMinnville, Ore.

[Signed] James H. Wilcox (Water Well Contractor)

Contractor's License No. 428 Date Mar. 19, 19 69