

RECEIVED
AUG 29 1967

NC

YAMH
5673

cac

NOTICE TO WATER WELL CONTRACTOR
The original and first copy
of this report are to be
filed with the

WATER WELL REPORT

State Well No. 4/4w-11

STATE ENGINEER, SALEM, OREGON 97310
within 30 days from the date
of well completion.
ENGINEER OF OREGON
(Please type or print)
OREGON

G-4715

State Permit No.

(1) OWNER:
Name Paul Youngman
Address Rte. 2 Box 127, McMinnville, Ore

(11) WELL TESTS: Drawdown is amount water level is lowered below static level
Was a pump test made? Yes No If yes, by whom?

(2) LOCATION OF WELL:
County Yamhill Driller's well number
SW 1/4 SW 1/4 Section 11 T. 4S. R. 4W W.M.
Bearing and distance from section or subdivision corner

Yield: gal./min. with ft. drawdown after hrs.
" " " " "
" " " " "
Comp. test 30 gal./min. with 60 ft. drawdown after 2 hrs.
Artesian flow g.p.m. Date
Temperature of water 54 Was a chemical analysis made? Yes No

(3) TYPE OF WORK (check):
New Well Deepening Reconditioning Abandon
In abandonment, describe material and procedure in Item 12.

(12) WELL LOG: Diameter of well below casing 0
Depth drilled 100 ft. Depth of completed well 100 ft.

(4) PROPOSED USE (check): (5) TYPE OF WELL:
Domestic Industrial Municipal Rotary Driven
Irrigation Test Well Other Cable Jetted
Dug Bored

Formation: Describe by color, character, size of material and structure, and show thickness of aquifers and the kind and nature of the material in each stratum penetrated, with at least one entry for each change of formation.

(6) CASING INSTALLED:
6" Diam. from 0 ft. to 100 ft. Gage .250
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

MATERIAL	FROM	TO
Topsoil	0	3
Brown Clay	3	33
Blue Clay, Silty	33	53
Blue Clay, and layers of Red		
Silty Clay	53	68
Med. Black & Brown Sand	68	74
Sandy Brown Clay	74	83
Fine to Med. Brown Gravel	83	97
Soft Blue Shale	97	100

(7) PERFORATIONS:
Perforated? Yes No
Type of perforator used Torch
Size of perforations 3/16 in. by 12 in.
78 perforations from 87 ft. to 100 ft.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.

Work started Aug. 1 1967 Completed Aug. 4 1967
Date well drilling machine moved off of well Aug. 4 1967

(8) SCREENS: Well screen installed? Yes No
Manufacturer's Name
Type Model No.
Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(13) PUMP:
Manufacturer's Name
Type: H.P.

(9) CONSTRUCTION:
Well seal—Material used in seal Cement Grout & Puddled Clay
Depth of seal 20 ft. Was a packer used? No
Diameter of well bore to bottom of seal 11 in.
Were any loose strata cemented off? Yes No Depth
Was a drive shoe used? Yes No
Was well gravel packed? Yes No Size of gravel: 3/8 Pea
Gravel placed from 20 ft. to 100 ft.
Did any strata contain unusable water? Yes No
Type of water? depth of strata
Method of sealing strata off

Water Well Contractor's Certification:
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

(10) WATER LEVELS:
Static level 28 ft. below land surface Date Aug. 4, 67
Artesian pressure lbs. per square inch Date

NAME Wilcox Drilling & Pump Co.
(Person, firm or corporation) (Type or print)
Address Box 569, McMinnville, Oregon
Drilling Machine Operator's License No. 172
[Signed] James H. Wilcox
(Water Well Contractor)
Contractor's License No. 428 Date Aug. 10, 1967