The original and first copy of this report are to be

YAMH No. 45/4W-246a nit No. ..

| filed with the | STATE E | NGINETER OF OREGON | | State | Well |
|--------------------------|--------------|--------------------------------|------|-------|--------|
| STATE ENGINEER, SALEM, O | REGONS ALEM. | ORES GRease type or print) | 5835 | State | Perm |
| of well completion | | (Do not write above this line) | | | . 0111 |

| (1) OWNER: | (10) LOCATION OF WELL: | | | |
|---|--|--|--|--|
| Name 1.6 I. Builders | County Yamhill Driller's well number 144 | | | |
| Address 1030 N. Baker St. | NE 34 S W Section 24 T. 43 R. 47 W.M. | | | |
| iclinnville. Oregon. | Bearing and distance from section or subdivision corner | | | |
| (2) TYPE OF WORK (check): | | | | |
| New Well ☐. Deepening ☐ Reconditioning ☐ Abandon ☐ | | | | |
| If abandonment, describe material and procedure in Item 12. | (11) WATER LEVEL: Completed well. | | | |
| (3) TYPE OF WELL: (4) PROPOSED USE (check): | Depth at which water was first found 53 | | | |
| Rotary D Driven D Domestic F Industrial Municipal | Static level 18 ff. below land surface. Date 6/16/2 | | | |
| Cable | | | | |
| Dug □ Bored □ Irrigation □ Test Well □ Other □ | Artesian pressure Ibs. per square inch. Date | | | |
| 5) CASING INSTALLED: Threaded Welded 5 "Diam. from 1 1 ft. to 118 ft. Gage .250 | (12) WELL LOG: Diameter of well below casing | | | |
| | | | | |
| "Diam. from | Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in | | | |
| | | | | |
| 3) PERFORATIONS: Perforated? Z Yes No. | position of Static Water Level and indicate principal water-bearing strata. | | | |
| Type of perforator used Torch | MATERIAL From To SWL | | | |
| Size of perforations 1/8 in. by 8 in. | Top Soil 1 0 2 | | | |
| 146 perforations from 58 tt. to 118 tt. | Yellow clay: 2 14 | | | |
| perforations fromft. toft. | Erown clav 14 38 | | | |
| perforations from ft. to ft. | Grav clav 38 53 | | | |
| | Black sand # 53 64 | | | |
| (7) SCREENS: Well screen installed? ☐ Yes ☐ No | Gine clay 64 68 | | | |
| Manufacturer's Name | Black sand - #1 68 80 | | | |
| Type Model No | Blue clay SS S4 | | | |
| Diam. Slot size Set from ft. to ft. | Black sand + 94 104 | | | |
| Diam. Slot size Set from ft. to ft. | Coarse black sand 1/8 in 104 112 | | | |
| (8) WELL TESTS: Drawdown is amount water level is lowered below static level | Blue clay 112 118 | | | |
| Was a pump test made? ☐ Yes ☐ No If yes, by whom? | | | | |
| Yield: gal./min. with ft. drawdown after hrs. | 7749 A | | | |
| | The state of the s | | | |
| <i>II</i> | The same and the s | | | |
| Bailer test 60 gal./min. with 109t. drawdown after 3 hrs. | | | | |
| Bailer lest (10 gai./mm. with 10/1t. drawdown after 9 ms. | | | | |
| Artesian flow g.p.m. | - / - / - / | | | |
| emperature of water Depth artesian flow encounteredft. | Work started 6/11/72 19 Completed 6/17/72 19. | | | |
| (9) CONSTRUCTION: | Date well drilling machine moved off of well 6/17/72 19 | | | |
| Well seal—Material used Coment Drilling Machine Operator's Certification: | | | | |
| Well sealed from land surface toft. | This well was constructed under my direct supervision. Materials used and information reported above are true to my | | | |
| Diameter of well bore to bottom of sealin. | best knowledge and belief. | | | |
| Diameter of well bore below sealin. | [Signed] Date Date (Drilling Machine Operator) | | | |
| Number of sacks of cement used in well seal 5 sacks | Drilling Machine Operator's License No. 200 | | | |
| Number of sacks of bentonite used in well sealsacks | | | | |
| Brand name of bentonite | Water Well Contractor's Certification: | | | |
| Number of pounds of bentonite per 100 gallons | This well was drilled under my jurisdiction and this report is | | | |
| of water lbs./100 gals. | true to the best of my knowledge and belief. | | | |
| Was a drive shoe used? ☐ Yes 戶 No Plugs Size: location ft. | Name Ted Schieler Vell Drilling (Person, firm or corporation) (Type or print) | | | |
| Did any strata contain unusable water? Yes No | STATES TO STANKING | | | |
| Type of water? depth of strata | Address Hall | | | |
| Method of sealing strata off | [Signed] Treodor W. Kehneln | | | |
| Was well gravel packed? Yes □ No Size of gravel: 3/3 | (Water Well Contractor) | | | |
| Gravel placed from 25 ft. to 118 ft. | Contractor's License No. 18 Date 4 19/ | | | |
| | · · · · · · · · · · · · · · · · · · · | | | |