NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

RECEIVED MAY 1 1968 STATE ENGINEER SALEM, OREGON

YAMH 5845

WATER WELL REPORT
STATE OF OREGON
(Please type or type)
(Do not write above this line)

State Well No. 4/4w-24 F

State Permit No. 66907

(1) OWNER:
Name Wilmer Andrist
Address 1353 Lafayette Ave., McMinnville Oregon

(2) TYPE OF WORK (check):
New Well ☒ Deepening ☐ Reconditioning ☐ Abandon ☐
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:
Rotary ☒ Driven ☐
Cable ☐ Jetted ☐
Dug ☐ Bored ☐

(4) PROPOSED USE (check):
Domestic ☒ Industrial ☐ Municipal ☐
Irrigation ☐ Test Well ☐ Other ☐

(5) CASING INSTALLED: Threaded ☐ Welded ☒
6" Diam. from 0 ft. to 116 ft. Gage .250
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

(6) PERFORATIONS: Perforated? ☒ Yes ☐ No.
Type of perforator used Torch
Size of perforations 3/16 in. by 12 in.
60 perforations from 105 ft. to 116 ft.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS: Well screen installed? ☐ Yes ☒ No
Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WATER LEVEL: Completed well.
Static level 14 ft. below land surface Date Apr. 9 1968
Artesian pressure lbs. per square inch Date

(9) WELL TESTS: Drawdown is amount water level is lowered below static level
Was a pump test made? ☐ Yes ☒ No If yes, by whom?
Yield: gal./min. with ft. drawdown after hrs.
" " " "
" " " "
Bailer test 30 gal./min. with 46 ft. drawdown after 2 hrs.
Artesian flow g.p.m. Date
Temperature of water 54 Was a chemical analysis made? ☐ Yes ☒ No

(10) CONSTRUCTION:
Well seal—Material used Cement Grout & Puddled Clay
Depth of seal 19 ft.
Diameter of well bore to bottom of seal 12 in.
Were any loose strata cemented off? ☐ Yes ☒ No Depth
Was a drive shoe used? ☐ Yes ☒ No
Did any strata contain unusable water? ☐ Yes ☒ No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? ☒ Yes ☐ No Size of gravel: 3/8 Pea
Gravel placed from 19 ft. to 116 ft.

(11) LOCATION OF WELL:
County Yamhill Driller's well number
SE ¼ NW ¼ Section 24 T. 4S R. 4W W.M.
Bearing and distance from section or subdivision corner

(12) WELL LOG: Diameter of well below casing 0
Depth drilled 116 ft. Depth of completed well 116 ft.
Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level as drilling proceeds. Note drilling rates.

MATERIAL	From	To	SWL
Topsoil	0	2	
Brown Clay	2	28	
Blue Clay	28	47	
Compacted Fine Sand	47	51	
Blue Clay	51	81	
Sand (with Wood)	81	84	
Blue Clay	84	102	
Sand & Fine Gravel	102	109	
Blue Clay	109	116	

Work started Apr. 3 1968 Completed Apr. 10 1968
Date well drilling machine moved off of well Apr. 10 1968

Drilling Machine Operator's Certification:
This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] James H. Wilcox (Drilling Machine Operator) Date Apr. 28 1968
Drilling Machine Operator's License No. 172

Water Well Contractor's Certification:
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
NAME Wilcox Drilling & Pump Co. (Person, firm or corporation) (Type or print)
Address P. O. Box 569, McMinnville, Oregon
[Signed] James H. Wilcox (Water Well Contractor)
Contractor's License No. 428 Date Apr. 28, 1968

(USE ADDITIONAL SHEETS IF NECESSARY)