NOTICE TO WATER WELL CONTRACTOR
The original and first copy
of this report are to be
filed with the

## RECEIVETA WELL REPORT YAMH

•	. 1
State Well No.	4/5W - 36

filed with the

STATE ENGINEER, SALEM, OREGON 9735 EP - 1 1970 THE OF OREGON
(Please type or print)
within 30 days from the date STATE ENGINEER above this line) SALEM. OREGON

State Permit No. ..

(1) OWNER:	(10) LOCATION OF WELL:
Name ( ) Mangel ( )	County Janeth Driller's well number /6 &
Address of 1 Ox 282 Milliamuss	a 1/4 1/4 Section 3 6 T. 45 R. 5 W W.M.
Oxe 97128	Bearing and distance from section or subdivision corner
(2) TYPE OF_WORK (check):	
New Well   Deepening □ Reconditioning □ Abandon □	
If abandonment, describe material and procedure in Item 12.	(44) YEARING TEXTEL C. I.A. I.
	(11) WATER LEVEL: Completed well.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 55 ft.
Rotary Driven Domestic Industrial Municipal D	Static level ft. below land surface. Date 8
Cable Jetted   Irrigation Test Well Other	Artesian pressure lbs. per square inch. Date
	The control of the co
CASING INSTALLED: Threaded Welded	(12) WELL LOG: Diameter of well below casing
" Diam. from Off. to 55 Aft. Gage 4	The second of th
ft. Gage	Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated,
	with at least one entry for each change of formation. Report each change in
PERFORATIONS: Perforated?   Yes   No.	position of Static Water Level and indicate principal water-bearing strata.
be of perforator used	MATERIAL From To SWL
	Top soil 1 0 2
Size of perforations in. by in.	16 10 10 10 10 10 10 10 10 10 10 10 10 10
perforations from ft. to ft.	agración serio
perforations from ft. to ft.	ville pelay.
perforations from ft. to ft.	gravel & green clay 55 60
	1
(7) SCREENS: Well screen installed?   Yes No	
Manufacturer's Name	trage 1.
Type Model No	₹.
Diam Slot size Set from ft. to ft.	
Diam Slot size Set from ft. to ft.	100
,	.5
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	
Was a pump test made?  Yes No If yes, by whom?	
Yield: gal./min. with ft. drawdown after hrs.	
" " "	.11 /
" " "	
Bailer test / 7 gal./min. with 22 ft. drawdown after 2 hrs.	=
Artesian flow g.p.m.	
	95 20 8-8 120
Temperature of water Depth artesian flow encountered ft.	Work started 8 - S 19/O Completed 8 - S 19/O Comple
CONSTRUCTION:	Date well drilling machine moved off of well 8 19
Well seal—Material used Communication	Drilling Machine Operator's Certification:
45	This well was constructed under my direct supervision.
Well sealed from land surface to ft.	Materials used and information reported above are true to my
Diameter of well bore to bottom of seal in.	best knowledge and belief.
Diameter of well bore below seal in.	[Signed] # obest & Sulbern Date 8-30, 1970
Number of sacks of cement used in well seal sacks	Drilling Machine Operator's License No. 337
Number of sacks of bentonite used in well seal sacks	Drining machine Operator's Internet 110.
Brand name of bentonite	Water Well Contractor's Certification:
Number of pounds of bentonite per 100 gallons	
of water lbs./100 gals.	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Was a drive shoe used? Yes \( \subseteq No \) Plugs Size; location ft.	DILLE Water Dr. 11 na Co
Did any strata contain unusable water?   Yes No	Name (Ferson, firm or corporation) (Type or print)
	Address KT 1 BX75 DAYTON, Ore
	11 0 - 0 - 10
Method of sealing strata off	[Signed] 1 obout & helbure
Was well gravel packed?   Yes No Size of gravel:	(Water Well Contractor)
Gravel placed from ft. to ft.	Contractor's License No. 4/ / Date, 19/C