O MAINAL File Original and Duplicate with the STATE ENGINEER, SALEM, OREGON

YAMH 6395

WATER WELL REPORT . STATE OF OREGON

State Permit No. G-1597

	(1) OWNER:	(11) WELL 7	TESTS: Drawdor lowered	wn is amount w below static lev	vater level vel	l is
3	Name Mr. Robert Stockhoff	Was a pump test r	nade? 🗌 Yes 🗶 No	f yes, by whon	1?	
	Address Dayton, Oregon	Yield:	gal./min. with	ft. drawdow	n after	hrs.
		,,	"	11		**
•	(a) LOCATION OF WELL, #	***	"	**		***
	(2) LUCATION OF WELL:	Bailer test 10	gal./min. with 15	ft. drawdow	n after 2	hrs.
	County Yamhill Owner's number, if any—	Artesian flow	g.p.m	. Date		
	1/30-A, 1/4 Section 6 T. 5-S R. 3-W W.M.	Temperature of v	vater Was a chemi	cal analysis ma	ide? 🗌 Y	es 🗌 No
	Bearing and distance from section or subdivision corner	// //			6	
	FENTEXX 300 ft.E.of W. line	(12) WELL]		eter of well		inches.
	175 ft. S. of N. line			of completed w		37 ft.
	5-S-3W Sec. 6 Se4 Nw 4	Formation: Description of the second statement of the second seco	ribe by color, character, f aquifers and the kind	size of materio	ıl and stru the mater	icture, and ial in each
		stratum penetrate	ed, with at least one er	try for each c	hange of	formation.
			MATERIAL		FROM	то
	TYPE OF WORK (check):	clay			0	5
		brown silt	;		5	21
	New Well Deepening Reconditioning Abandon I If abandonment, describe material and procedure in Item 11.	blue clay			27	3 8
	it abandoninent, describe indicate and pro-		ed blue sand		38	50
	(4) PROPOSED USE (check): (5) TYPE OF WELL:	blue clay			50	52
	stic Industrial Municipal Rotary Driven		sand silt		52	60
	Industrial Cable	blue sand			60	77
		blue clay			77	81
	(6) CASING INSTALLED: Threaded □ Welded \		silt some brown	spots	81	87
6	5/8 od Diam from 0 ft. to 87 ft. Gage 17.02					
	7					
	(7) PERFORATIONS: Perforated? Yes I No					
	Type of perforator used cutting torth		DEC.	BINE		
	SIZE of perforations in. by 12 in. perforations from 36 ft. to 87 ft.			MAN B Q 1		
	2 Rows perforations from ft. apartit to ft.		Tra DF(<u>, 16 1957</u>	مست	
	perforations from ft. to ft.		STATE	ENCIN	ER	
			CALE	W, OREGO	18.3	
	perforations fromft. toft.		- Unlik	n) OILEG	1	_
	perforations from ft. to ft.				——	_
	(SCREENS: Well screen installed Yes No					1
	afacturer's Name				-	
	Type Model No.		•		-	
	Diam Slot size Set from ft. to ft.					<u> </u>
	Diam, Slot size Set from ft, to ft,	Work started	lov. 8 157.	Completed N	ov. 1	1957
	201 7 7 0 05 71	(13) PUMP:				
	COXIDENTOCHER	1 '				
	Was well gravel packed? X Yes □ No. Size of gravel: 10.3/1.		Name			
	Gravel placed from 18 ft. to 87 ft.	1			. п.г	
	Was a surface seal provided? X Yes □ No To what depth 16-18 ft. Material used in seal— cemented	Well Driller's	Statement:			
	Did any strata contain unusable water? Yes X No		was drilled under m	v jurisdiction	and thi	s report is
		true to the bes	st of my knowledge a	nd belief.		-
		36	THE TERMS CHEVE	TTMO		
	Method of sealing strata off	NAMEM	(Person, firm, or corpo	ration) (Type or p	rint)
	(10) WATER LEVELS:	Address 290	02 Portland Rd.	Newberg	Orego	m
	Static level 18 ft. below land surface Date	- 1	_			
	Artesian pressure Ibs. per square inch Date	Driller's well	ylumber	<i>711</i>	<u>.</u>	
	Log Accepted by:	[FO:3]	el XIC	11/00	lou	/
	Signed Robert & Stockhoff 22 nov. 1957	[Signed]	(Well	Dfiller)	F.,. 	
	[Signed] Worth 1951	License No	111	DateNov	r. 14	, 195.7.
	Comments of the comments of th	· //				