RECEEVED MAR 13 1832

File Original and First Copy with the STATE ENGINEER, SALEM, OREGON

STATE E GINEER

-WATER WELL REPORT STATE OF OREGON

DITUDIN, OXIZOOTI				
(1) OWNER:		(11) WELL TESTS: Drawdown is amount we lowered below static levers.	zater level	is
Name Robert Stockhoff		Was a pump test made? ▼ Yes ☐ No If yes, by whom	, Meeke	r
Address Rt 1 Box 32		Yield: 200 gal./min. with 100 ft. drawdown		
Dayton, Oregon		27 29 29		,,
(2) LOCATION OF WELL: ## 3	₹	yy yy 11		***
County Yamhill Owner's number, if any—		Bailer test gal./min. with ft. drawdown after hrs. Artesian flow g.p.m. Date		
Bearing and distance from section or subdivisi	ion corner	(10) WITH T TOO.	10	
		(12) WELL LOG: Diameter of well		inches.
		Formation: Describe by color, character, size of materia show thickness of aquifers and the kind and nature of t stratum penetrated, with at least one entry for each cl	the materio	il in each
			FROM	TO
		MATERIAL	O	<u> </u>
(3) TYPE OF WORK (check):		Blue clay	٠,	72
New Well Deepening Reconditioning Abandon		Brown sand silt	20	
Is bandonment, describe material and proced	lure in Item 11.	blue clay silt	12	32
(4) PROPOSED USE (check):	(5) TYPE OF WELL:	Caving blue clay and sand blue sand silt	32 35	<u>35</u> 66
	, ,	blue clay	66	72
Domestic Industrial Municipal	Cable 🖺 Jetted 🗌	brown sand silt	72	83
Irrigation II Test Well Other	Dug 🗌 Bored 🗎	blue sand silt	83	95
(6) CASING INSTALLED: Threaded □ Welded ▼				7/2
0 3/40D Diam from 0 ft. to kx 122 ft. Gage 28.041bs		kax light brown sand silt (coarse Red clay sticky	107	122
ft. Gage ft. com		ned cray sorcky		
"Diam. from ft. to				
		172		
(i) I milit omizzionia	erforated? 🏝 Yes 🔲 No			
Type of perforator used cutting tor	7.0			
FOWS perforations 1/4 in. by POWS 20	10 in.			
perforations from				
perforations from ft. to ft ft ft.				
perforations from perforations				
perforations from	16. 00			
(8) SCREENS: Well screen	installed 🗌 Yes 🏖 No			
Manufacturer's Name			ļ	
Type Model No				
Slot size Set from ft. to ft.				
Slot size Set from ft. to ft.		work startedFebruary 21 19 . CompletedMan	? 8	19 62
(9) CONSTRUCTION: 16" h	nole	(13) PUMP:		
(a) Constituent.		1 ' '		
Was well gravel packed? ★ Yes □ No Size of gravel: 1/2 to 1/2 Gravel placed fromft. toft.		Manufacturer's Name		
Was a surface seal provided? Yes No To what depth? ft.		Type:	*****	
Material used in seal—		Well Driller's Statement:		
Did any strata contain unusable water?	Yes 🧏 No	This well was drilled under my jurisdiction	and this	report is
Type of water? Depth of strata		true to the best of my knowledge and belief.		
Method of sealing strata off	Experience of the second second	NAME MEEKER WELL DRILLING		
(40) YEV A INVESTED T TOTAL CL.		(Person, firm, or corporation) (Type or print)		
(10) WATER LEVELS:		Address 2902 Hoover Blvd., XXX Newberg, Oregon		
Static level 15 ft. below land surface Date 3/8-62				
Artesian pressure lbs. per sq	uare inch Date	Driller's well number	<i>j</i>	
Log Accepted by:		[Signed] John H Mu	ku	<i></i>
		(Well Driller)	_ Ω	40
[Signed] Date	;, 19	License No. 111 Date Mar	. 0	, ₁₉ 62
		•		