

NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the

WATER RESOURCES DEPARTMENT,
SALEM, OREGON 97310
within 30 days from the date
of well completion.

RECEIVED WATER WELL REPORT

OCT 9 1978

STATE OF OREGON
(Please type or print)

WATER RESOURCES DEPT.
SALEM, OREGON

YAMH
6501

State Well No. 55/3w76bd
State Permit No. G-8464

(1) OWNER:

Name Donald Kuhn
Address RT 1 DAYTON, ORE

(2) TYPE OF WORK (check):

New Well Deepening Reconditioning Abandon
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary Driven
Cable Jetted
Dug Bored

(4) PROPOSED USE (check):

Domestic Industrial Municipal
Irrigation Test Well Other

CASING INSTALLED:

Threaded Welded
10" Diam. from 0 ft. to 150 ft. Gage 1/4
" Diam. from _____ ft. to _____ ft. Gage _____
" Diam. from _____ ft. to _____ ft. Gage _____

PERFORATIONS:

Perforated? Yes No.
Type of perforator used TORCH
Size of perforations 1/4 in. by 6 in.
260 perforations from 110 ft. to 150 ft.
perforations from _____ ft. to _____ ft.
perforations from _____ ft. to _____ ft.

(7) SCREENS:

Well screen installed? Yes No
Manufacturer's Name _____
Type _____ Model No. _____
Diam. _____ Slot size _____ Set from _____ ft. to _____ ft.
Diam. _____ Slot size _____ Set from _____ ft. to _____ ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level
Was a COMP test made? Yes No If yes, by whom? DRILLER
Yield: 300 gal./min. with 70 ft. drawdown after 8 hrs.
" " " " " "
" " " " " "
Bailer test _____ gal./min. with _____ ft. drawdown after _____ hrs.
Artesian flow _____ g.p.m.
Temperature of water _____ Depth artesian flow encountered _____ ft.

(9) CONSTRUCTION:

Well seal—Material used CEMENT
Well sealed from land surface to 20 ft.
Diameter of well bore to bottom of seal 16 in.
Diameter of well bore below seal 16 in.
Number of sacks of cement used in well seal 11 sacks
How was cement grout placed? PUMPED
Was a drive shoe used? Yes No Plugs _____ Size _____ location _____ ft.
Did any strata contain unusable water? Yes No
Type of water? _____ depth of strata _____
Method of sealing strata off _____
Was well gravel packed? Yes No Size of gravel: 3/4
Gravel placed from 20 ft. to 150 ft.

(10) LOCATION OF WELL:

County Yamhill Driller's well number 592
1/4 Section 16 T. 55 R. 3W W.M.
Bearing and distance from section or subdivision corner _____

(11) WATER LEVEL: Completed well.

Depth at which water was first found 50 ft.
Static level 50 ft. below land surface. Date 9-26-78
Artesian pressure _____ lbs. per square inch. Date _____

(12) WELL LOG:

Diameter of well below casing 0
Depth drilled 150 ft. Depth of completed well 150 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
TOP SOIL	0	2	
BROWN CLAY	2	32	
BLUE CLAY	32	50	
FINE BLACK SAND	50	55	
BLUE CLAY	55	90	
BLACK SAND	90	110	
SAND & GRAVEL	110	147	
BLUE CLAY	147	150	

Work started 9-18 19 78 Completed 9-26 19 78
Date well drilling machine moved off of well 9-26 19 78

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] Robert Schelburne Date 10-2, 19 78
(Drilling Machine Operator)

Drilling Machine Operator's License No. 337

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

Name BLUE WATER DRILLING CO
(Person, firm or corporation) (Type or print)

Address RT 1 BX 75 DAYTON, ORE

[Signed] Robert Schelburne
(Water Well Contractor)

Contractor's License No. 417 Date 10-2, 19 78