NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON 97310 STATE OF OREGONG-within 30 days from the date of well completion.

(Please type of the date of well completion)

STATE OF OREGON -6/39
(Please type or print) G 32-93 State Permit No. ..

or wen completion.	93-73		
(1) OWNER:	(11) WELL TESTS: Drawdown is amount lowered below static le	water level	. is
Name James Shelbarne	Was a pump test made? ✓ Yes ☐ No If yes, by whom? ☐ // er		
Address RTI Dayton	Yield: 650 gal./min. with 25 ft. drawdov		/ O hrs.
	39 39 39		"
(2) LOCATION OF WELL:	1) 11 11		***************************************
Van 1'11 26	Bailer test gal./min. with ft. drawdo	own after	hrs.
County / G/M / Driller's well number & C N/// 14 5(1) 14 Section / G T. 5 & R. 3 W. W.M.	Artesian flow g.p.m. Date		
10 14 000 12	Temperature of water Was a chemical analysis	made? 🔲 🏾	es 🛂 No
Bearing and distance from section or subdivision corner	(12) WELL LOG: Diameter of well below of	asing	0
The second secon	Depth drilled /40 ft. Depth of completed w	rell / 4	්ර ft.
	· · · · · · · · · · · · · · · · · · ·	ST STATES	APPROXIMATION AND A SECOND
	Formation: Describe by color, character, size of materishow thickness of aquifiers and the kind and nature of stratum penetrated, with at least one entry for each of	the materi change of	al in each
		[ I	
(3) TYPE OF WORK (check):	MATERIAL TARREST	FROM	TO
Yew Well	107 301	<u> </u>	<u></u>
andonment, describe material and procedure in Item 12.	Brown Clay	12-	525
	Block	25	30
(4) PROPOSED USE (check): (5) TYPE OF WELL:	Blue Clay	55	90
Domestic   Industrial   Municipal   Rotary   Driven   Cable   Jetted	Black Sand	90	110
Irrigation Test Well Other Dug Bored	500d 1 Arono 1	111	134
(c) CACING INSTALLED.	DINE CIAV	134	12/2
(6) CASING INSTALLED: Threaded Welded	8105 6109	107	170
10 "Diam. from 0 ft. to 190 ft. Gage/ 25-3		· · ·	
"Diam. fromft. to ft. Gage		<u> </u>	
"Diam, from ft, to ft. Gage		<del> </del>	
(7) PERFORATIONS: Perforated? Pyes   No		-	
Type of perforator used Torch			
Size of perforations 4 in. by 6 in.			
1200 perforations from 40 ft. to 140 ft.	HELLER		
perforations from	AUG 1 6 1965		
perforations from ft. to ft.	Market to the state of the stat		
perforations from ft. to ft.	STATE CHIGINEER		
perforations fromft. toft.	SALEM, OREGON		
(8) SCREENS: Well screen installed? ☐ Yes ☐ No		·	
Manufacturer's Name			
Model No.			
Slot size	Work started 6 - 5 1965 Completed 6	-15	1965
Diam. Slot size Set from ft. to ft.	Date well drilling machine moved off of well 6 -	15	1965
(9) CONSTRUCTION:	(13) PUMP:		
Well seal—Material used in seal Cement	Manufacturer's Name Jacuzzi		
Depth of seal	11146160	5	-0
Diameter of well bore to bottom of sealin.	Type: H.P. S		
Were any loose strata cemented off?   Yes No Depth	Water Well Contractor's Certification:		
Was a drive shoe used? ☐ Yes ☑ No	This well was drilled under my jurisdiction	and this	renort is
Was well gravel packed? Yes [] No Size of gravel:	true to the best of my knowledge and belief.	and tins	report is
Gravel placed from 20 ft. to 40 ft.	Plac WATER	ファン	line
Did any strata contain unusuable water?   Yes	NAME (Person, firm or corporation) (Type or print)		
Type of water? depth of strata	Address RTI BX75 DQY	Ton.	Ore
Method of sealing strata off	1-4	7=7	327
(10) WATER LEVELS:	Drilling Machine Operator's License No		
	[Signed] Nobel Shilbutte		
Static level 30 ft. below land surface Date 6-15-65	(Water Well Contractor)		
Artesian pressure lbs. per square inch Date	Contractor's License No. 4 Date	O	19. <i>6.5</i>