NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

WATER RESOURCES DEPARTMENT, SALEM, OREGON 97310 witkin 30 days from the date of well completion.

WATER WELL REPORT

STATE OF OREGON

(Please type or print) (Do not write above this line) YAMH

6744	State Well No. $55/3\omega-28$
	State Permit No

(1) OWNER:	(10) LOCATION OF WELL:		
Name CARLTON NURSERY	County / 4m h; // Driller's well number	. 69c	2
Address PT/		76	W.M.
DAYTON, OR	Bearing and distance from section or subdivision of		
(2) TYPE OF WORK (check):			
New Well Deepening Reconditioning Abandon			
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.		
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 55	•	ft.
Rotary Driven Domestic Industrial Municipal	Static level 50 ft. below land surfa-	ce. Date 5-	9-80
☐ Bored ☐ Irrigation ☐ Test Well ☐ Other ☐	Artesian pressure lbs. per square inc		
(5) CASING INSTALLED: Threaded Welded Welded	(12) WELL LOG: Diameter of well below Depth drilled 50 ft. Depth of completed Formation: Describe color, texture, grain size and show thickness and show the show the show that the show that the show the	well /5	oft.
(6) PERFORATIONS: Perforated? Yes No.	and show thickness and nature of each stratum ar with at least one entry for each change of formation. position of Static Water Level and indicate principal	Report soch	ahanes in
Type of perforator used TORCh	MATERIAL Fr	om To	SWL
Size of perforations /4 in. by 6 in.	TOP SOIL	13	
400 perforations from 90 ft. to 150 ft.	BROWN CIAY 3	14	
perforations from ft. to ft.	Blue CIAY 14	55	
perforations from ft. to ft.	BIACK SAND 53	-60	
(7) SCREENS: Well screen installed? Yes	BIOC CIAV	5 95	
Manufacturer's Name	SAND OF RAVE!	5/30	 ,
Type Model No.	01000144	2/50	
Diam Slot size Set from ft. to ft.			
Diam Slot size Set from ft. to ft.			
(8) WELL TESTS: Drawdown is amount water level is	770		
Comp Jowered below static level	- KECHWED		
s a pump-test made? Yes No If yes, by whom? ORI //CR	1:27/00/1000		
rield: 350 gal./min. with 56 ft. drawdown after 8 hrs.	<u> </u>		
" " "	WATER RESOURCES DEPT		
" " "	SALEM. OREGON		
Bailer test gal./min. with ft. drawdown after hrs.			
esian flow g.p.m.			
Temperature of water Depth artesian flow encountered ft.	Work started 3- 5 1880 Completed 5	-9	1950
(9) CONSTRUCTION:	Date well drilling machine moved off of well	-9	1980
Well seal-Material used CEMPAT GROUT	Drilling Machine Operator's Certification:		
Well sealed from land surface toft.	This well was constructed under my dire	ct super	vision.
Diameter of well bore to bottom of seal in.	Materials used and information reported above best knowledge and belief.	e are true	to my
Diameter of well bore below seal in.	[Signed] A Lotte Date	5-24	- 19 80
Number of sacks of cement used in well seal sacks How was cement grout placed? PUMPEO	Drilling Machine Operator) Drilling Machine Operator's License No.		, 20
All The State of t			
Activities of the second secon	Water Well Contractor's Certification:		
Was a drive shoe used? \(\sqrt{V} \rightarrow \)	This well was drilled under my jurisdiction true to the best of my knowledge and belief.	and this re	eport is
Was a drive shoe used? ☐ Yes ☐ No Plugs Size: location ft. Did any strata contain unusable water? ☐ Yes ☐ No	Name 6/UC WATER DR	11/11	9 00
Type of materia	Person, firm or corporation	(Type or prin	B
- dopin of strata	Address 1. DX 15 DF 10	J, OR	Name -
Method of sealing strata off Was well gravel packed? ✓ Yes ☐ No Size of gravel: 4	[Signed] Robert & Albagno	2	********
Gravel placed from 20 11	(Water Well Contractor)	4 1/	O
Gravel placed from	Contractor's License No. 4. Date 5	 4	ر مرور ,