YAMH 6754

NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the STATE ENGINEER, SALEM 10, OREGON within 30 days from the date of well completion.

WATER WELL REPORT
STATE OF OREGON
(Please type or print)

63104

State Well No. 5/3W-29 F

State Permit No. 6-8823

(1) OWNER:

Name Robert L. Janzen

Address Rt. 2, Box 69
Dayton, Oregon 97114

(2) LOCATION OF WELL: #1

County Yamhill Driller's well number

S.E.¼ N.W.¼ Section 29 T. 5S R. 3W W.M.

Bearing and distance from section or subdivision corner

(3) TYPE OF WORK (check):

New Well ☒ Deepening ☐ Reconditioning ☐ Abandon ☐

If abandonment, describe material and procedure in Item 12.

(4) PROPOSED USE (check):

Domestic ☐ Industrial ☐ Municipal ☐
Irrigation ☒ Test Well ☐ Other ☐

(5) TYPE OF WELL:

Rotary ☐ Driven ☐
Cable ☐ Jetted ☐
Dug ☐ Bored ☒

(6) CASING INSTALLED: Threaded ☐ Welded ☐

12" Diam. from 9 ft. to 24 ft. Gage 1/4"
Pit 4 by 6 ft. Diam. from 1/9/ ft. to 9 ft. Gage 6 in.
" Diam. from ft. to ft. Gage concrete

(7) PERFORATIONS: Perforated? ☐ Yes ☒ No

Type of perforator used

Size of perforations in. by in.

perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.

(8) SCREENS: Well screen installed? ☐ Yes ☒ No

Manufacturer's Name

Type Model No.

Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(9) CONSTRUCTION: Dug out to blue clay,

Well seal—Material used in seal sealed with cement

Depth of seal 5 ft. ft. Was a packer used? No

Diameter of well bore to bottom of seal 30 in.

Were any loose strata cemented off? ☐ Yes ☒ No Depth

Was a drive shoe used? ☐ Yes ☒ No

Was well gravel packed? ☐ Yes ☒ No Size of gravel:

Gravel placed from ft. to ft.

Did any strata contain unusable water? ☐ Yes ☒ No

Type of water? Depth of strata

Method of sealing strata off

(10) WATER LEVELS:

Static level 6 ft. below land surface Date July, '64

Artesian pressure lbs. per square inch Date

(11) WELL TESTS: Drawdown is amount water level is lowered below static level

Was a pump test made? ☒ Yes ☐ No If yes, by whom? Self

Yield: 150/min gal./min. with 25 ft. drawdown after 24 hrs.
" " " "
" " " "

Bailer test gal./min. with ft. drawdown after hrs.

Artesian flow g.p.m. Date

Temperature of water 45° Was a chemical analysis made? ☐ Yes ☒ No

(12) WELL LOG: Diameter of well below casing 12 in.

Depth drilled 36 ft ft. Depth of completed well 36 ft.

Formation: *Describe by color, character, size of material and structure, and show thickness of aquifers and the kind and nature of the material in each stratum penetrated, with at least one entry for each change of formation.*

MATERIAL	FROM	TO
Top soil	3 ft	
Blue clay	25 ft.	
Hard, black sand	2 ft.	
Black sand, fine	6 ft	

Work started 19 59 Completed 1964

Date well drilling machine moved off of well 19

(13) PUMP:

Manufacturer's Name Fairbanks Morse

Type: Centrifical H.P. 5

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

NAME Robert L. Janzen
(Person, firm or corporation) (Type or print)

Address Rt. 2, Box 69
Dayton, Oregon

Drilling Machine Operator's License No.

[Signed]
(Water Well Contractor)

Contractor's License No. Date , 19

(USE ADDITIONAL SHEETS IF NECESSARY)