File Original and First Copy with the STATE ENGINEER, SALEM, OREGON

STATE OF OREGON

WATER WELL REPORT 6755 State Well No. ...

State Permit No. ...

(1) OWNER:	(11) WELL TESTS: Drawdown is amount water level is
Name Fred Withee	lowered below static level
Address	Was a pump test made? Yes No If yes, by whom? Yield: 300 gal./min. with 85 ft. drawdown after 48 hrs.
	" " " " " " "
(A) T A A L T A L	21 12 21 21
(2) LOCATION OF WELL:	Bailer test gal./min. with ft. drawdown after hrs.
County Manhill Owner's number, if any—	Artesian flow g.p.m. Date
5W 14/3E 14 Section 29 T. 35 R. 3W W.M.	Temperature of water
Bearing and distance from section or subdivision corner	
	(12) WELL LOG: Diameter of well inches.
	Depth drilled //9 ft. Depth of completed well //4 ft.
Andrew Control of the	Formation: Describe by color, character, size of material and structure, and show thickness of aquifers and the kind and nature of the material in each
	stratum penetrated, with at least one entry for each change of formation.
	MATERIAL FROM TO
(3) TYPE OF WORK (check):	Top Soil 0 2
New Well Deepening Reconditioning Abandon	Brown Clay 229
If abandonment, describe material and procedure in Item 11.	Blue Clay 29 42
TOPOGRAP TICE (I . I). (// MYDE OF YURI I .	Comported Fine Sond 42 36
ROPOSED USE (check): (5) TYPE OF WELL:	Sand Med to coarce 56 73
Domestic Industrial Municipal Rotary	Blue C/=1 73 99
Irrigation Test Well Other Dug Bored	Fine Grabel 99 113
	Hard Blue May 115 119
(6) CASING INSTALLED: Threaded □ Welded	775-15-15-15-15-15-15-15-15-15-15-15-15-15
"Diam. from Oft. to // le ft. Gage H. Well	
ft. Gage ft. Gage	Well Should be pumbed for
Ti. Gage ft. Gage	about 30 days before putting in seal
	to out orarel pleased.
(7) PERFORATIONS: Perforated? Yes No	To go graver provide
Type of perforator used /orch	= :
SIZE of perforations /2 in. by in. 8	
304 perforations from 57 ft. to 72 ft.	
125 perforations from 92 ft. to 114 ft.	
perforations from ft. to ft.	
perforations from ft. to ft.	
perforations fromft. toft.	
SCREENS: Well screen installed Yes No	
Manufacturer's Name	
Type Model No.	
Diam, Slot size Set from ft. to ft.	
Slot size Set from ft, to ft.	Work started Hug 23 1962 Completed Hue 29 1963
(9) CONSTRUCTION:	(13) PUMP:
Was well gravel packed? X Yes 🗆 No Size of gravel:	Manufacturer's Name
Gravel placed from ft. to ft.	Type: H,P.
Was a surface seal provided? 🗌 Yes 📋 No To what depth? ft.	
Material used in seal—	Well Driller's Statement:
Did any strata contain unusable water? 🗌 Yes 🗍 No	This well was drilled under my jurisdiction and this report is
Type of water? Depth of strata	true to the best of my knowledge and belief.
Method of sealing strata off	NAME Wileax Drilling Co.
(10) WATER LEVELS:	(Person, firm, or corporation), (Type or print)
Static level 19' ft. below land surface Date	Address P.D. Bay 549 McMinnville, Orci
Artesian pressure lbs. per square inch Date	# 3
Arresian pressure ibs. per square men Dave	Driller's well number
Log Accepted by:	[Signed] James H. Welent By J. L. W.
[Signed] Fred Witherate How. 13, 1962	(Well Driller)
(Owner)	License No. 53 Date 70, 30, 1962