NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the

## WATER WELL REPORT ANH STATE OF OREGON

•		- /
Stafe	Well No	56/3W-30
State	Permit No.	

WATER RESOURCES DEPARTMENT, STATE OF SALEM, OREGON 97310 (Please type within 30 days from the date of well completion. (Do not write at	e or print) State Permit N	5 s / 3 w - 3 0	
	1 (10) 2 0 2 1		
(1) OWNER:	(10) LOCATION OF WELL:		
Name Hopewell Church	County / Am Mi / Driller's well number 650		
Address R / ( )	14 14 Section 30 T. 55 R. 3W W.M.		
(a) Myne of Work (1-1)	Bearing and distance from section or subdivisi	on corner	
(2) TYPE OF WORK (check):	-	to the second se	
New Well Deepening Reconditioning Abandon			
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.		
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 2/0 ft.		
Rotary Driven Domestic Industrial Municipal Domestic	Static level 95 ft. below land surface. Date 7-31. 79		
Dug   Bored   Irrigation   Test Well   Other	Artesian pressure lbs. per squar	e inch. Date	
CASING INSTALLED: Threaded Welded			
CASING INSTALLED: Threaded Welded Welded Welded Street Threaded Th	(12) WELL LOG: Diameter of well below casing		
# Diam from O ft. to 30 ft. Gage/60#	Depth drilled 230 ft. Depth of completed well 230 ft.		
"Diam from tt. to ft. Gage	Formation: Describe color, texture, grain size and structure of materials;		
	and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in		
PERFORATIONS: Perforated? Yes No.	position of Static Water Level and indicate prin	cipal water-bearing strata.	
Type of perforator used 5 \$\textit{A} \cdots\$	MATERIAL	From To SWL	
Size of perforations /4 in. by 6 in.	TOP SOIL	02	
100 perforations from 190 ft. to 230 ft.	BROWN CLAY	2 30	
perforations from ft. to ft.	SOFT RED ROCK	20 30	
perforations from ft. to ft.	BROKERROCK	30 35	
(7) SCREENS: Well screen installed?   Yes   No	med Brown Rock	35 45	
Manufacturer's Name	FOFT PROUNT PACK	V5 /35	
Type Model No.	HAPON OPEN DOCK	160 780	
Diam. Slot size Set from ft. to ft.	THE KU G RECT HOLD	60 230	
Diam Slot size Set from ft. to ft.			
(8) WELL TESTS: Drawdown is amount water level is fowered below static level	RECEIVED		
Was a numb test made? Yes \( \subseteq \text{No If yes, by whom?} \( \subseteq \mathcal{P} \) \( \subseteq \mathcal{P} \)	Δβς 3 - 1070		
Yield: 20 gal./min. with 100 ft. drawdown after / hrs.	1.000 1070		
" " "	WATER RESOURCES DEPT		
" " " " " " " " " " " " " " " " " " "	SALEM, OREGON		
Bailer test gal./min. with ft. drawdown after hrs.			
Artesian flow g.p.m.			
erature of water Depth artesian flow encountered ft.	Work started 7-29 1979 Complete	d 7-3/ 1978	
(9) CONSTRUCTION:	Date well drilling machine moved off of well	7-31 1979	
Well seal-Material used CemenT	Drilling Machine Operator's Certification:		
Well sealed from land surface to 65 ft.	This well was constructed under my	direct supervision.	
Diameter of well bore to bottom of seal	Materials used and information reported best knowledge and belief.	above are true to my	
Diameter of well bore below seal in.	[Signed] MMU PAMMIN	Date 8 - 4 19 79	
Number of sacks of cement used in well seal	(Drilling Machine Organator)	, 7 77	
How was cement grout placed? Pumped	Drilling Machine Operator's License No.		
	Water Well Contractor's Certification:	. <u></u> . <u></u>	
	This well was drilled under my jurisdiction and this report is		
Was a drive shoe used?   Yes No Plugs Size: location ft.	true to the best of my knowledge and bell	かりにカーハス	
Did any strata contain unusable water?   Yes No	Name (Person, firm or corporation)	(Type of print)	
Type of water? depth of strata	Address (T//3X25/)AY	TONJOK	
Method of sealing strata off	Balest & Mall	111	
Was well gravel packed? ☐ Yes ☑ No Size of gravel:	[Signed] (Water Well Contr.	actor)	
Gravel placed from ft. to ft.	Contractor's License No. 4/2 Date	1979	