STATE OF OREGON WATER WELL REPORT

(as required by ORS 537.765)

DECEIVED N SEP 13 1985

WATER RESOURCES DEPT PRINT IN INK SALEM. OREGON

4AMH 6784 55/3W-32 (for official use only)

(1) OWNER:	(10) LOCATION OF WELL by legal description:
D to Suland	VAnalii 32
Al	311
Address Kre. 1 50 x 556 City Salem State Oregon	Township Range Range WM.
	Tax Lot Lot Block Subdivision
(2) TYPE OF WORK (check):	MAILING ADDRESS OF WELL (or nearest address)
New Well ☐ Deepening ☐ Reconditioning ☐ Abandon ☐	
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL of COMPLETED WELL:
(3) TYPE OF WELL: (4) PROPOSED USE (check):	
Rotary Air Driven Domestic Industrial Municipal Thermal:	Static level ft. below land surface. Date 8-2,1-85
Rotary Mud Dug D Irrigation Withdrawal Reinjection D	Artesian pressure lbs. per square inch. Date
Cable Bored Piezometric Grounding Test	in the second se
CASING INSTALLED: Steel Plastic	(12) WELL LOG: Diameter of well below casing
Threaded Welded	Formation: Describe color, texture, grain size and structure of materials; and show thickness
"Diam. from ft. to ft. Gauge	and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal
ft. to ft. Gauge	water-bearing strata.
LINER INSTALLED: Steel Plastic Threaded Welded	MATERIAL From To SWL
Diam. from 105 ft. to 155 ft. Gauge 186	Existing easing extends to
	110's Originally drilled to
(6) PERFORATIONS: Perforated? Yes No	120: Cleaned out from
Size of perforations in. by in.	110'-120' Hagus began drilling:
perforations from ft. to ft.	
perforations from ft. to ft.	Citaly clay 120 132
perforations from ft. to ft.	Ked thrown clay 132 155 27
(7) SCREENS: Well screen installed? Yes No	
Manufacturer's Name	
Type Model No Model No.	
Diam Slot Size Set from ft. to ft.	
Diam Slot Size Set from ft. to ft.	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	
Was a pump test made? ☐ Yes ☐ No If yes, by whom?	4-
Was a point test made: I fee I fee in yes, by whom: Yield: gal./min. with ft. drawdown after hrs.	
" " " " "	7-
Air test gal./min. with drill stem at ft. hrs.	
Bailer test gal./min. with ft. drawdown after hrs.	
Artesian flow g.p.m.	and a second
Depth artesian flow encounteredft.	
(v) CONSTRUCTION: Special standards: Yes \(\subseteq \) No \(\subseteq \)	Date work started H. 2 85 /completed H. 22 85
Well seal-Material used DIHM Cement > Sand	Date well drilling machine moved off of well 1986
Well sealed from land surface to	(unbonded) Water Well Constructor Certification (if applicable):
Diameter of well bore to bottom of seal in.	This well was constructed under my direct supervision. Materials used and
Diameter of well bore below seal in.	information reported above are true to my best knowledge and belief.
Amount of sealing material sacks pounds D	[Signed] Date, 19
How was cement grout placed?Theaxaut Mixuas	(bonded) Water Well Constructor Certification:
powed from surface. There was not	Bond 94-97-960 Issued by: MARYLAND FIDELITY + DEPOSIT
any water in annulus, mix was rodded ino	(number) (Surety Company Name)
Was pump installed? Type HP Depth 109119	On behalf of (type or print name of Water Well Constructor)
Was a drive shoe used? ☐ Yes ☐ No Plugs Size: location	This wall was deilled under my invisition and this area to the state of
Type of Water? depth of strata	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief:
	Master all waldrown
Method of sealing strata off Was well gravel packed? ✓ Yes ☐ No Size of gravel: 3/2	(Signed) Water Well Constructor)
Gravel placed from	(Dated)
Carros provos acous managements programma to to management to	