NOTICE TO WATER WELL CONTRACTOR
The original and first copy

of this report are to be filed with the

WATER WELL REPORT () STATE OF OREGON (Please type or print)

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

(Do not write above this line TE I

1 19 19/4	FGL
ENGINEE Permit No.	4/8/19
OREGON	

(1) OWNER:	(10) LOCATION OF WELL:		
Name Amel Funk	County Yamhill Driller's well number		
Address Rte. 1 box 169, McMinnville, Or	e SW 14 NW 14 Section 3 T. 5S	_{R.} 4W w.м.	
	Bearing and distance from section or subdivision		
(2) TYPE OF WORK (check):	Scaring and absorbed from South		
New Well			
If abandonment, describe material and procedure in Item 12.	(11) TYADUND TENTET, Commission	_11	
	(11) WATER LEVEL: Completed well.		
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 63 ft.		
Rotary 💆 Driven 🗆 Domestic 🖂 Industrial 🖂 Municipal 🖂	Static level 26 ft. below land st	urface. Date $Nov. 10-72$	
Dug ☐ Bored ☐ Irrigation ☐X Test Well ☐ Other ☐	Artesian pressure lbs. per square	e inch. Date	
CASING INSTALLED: **Bo Diam. from 0 ft. to 97 ft. Gage	(12) WELL LOG: Diameter of well below casing 5 In. Depth drilled 130 ft. Depth of completed well 97 ft. Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.		
Morroh		From To SWL	
1 10	MATERIAL		
Size of perforations $\frac{1}{2}$ in. by $\frac{12}{12}$ in.	Topsoil Brown Clay	0 2 31	
120 perforations from 75 ft. to 95 ft.	Decomposed Clay, red &		
perforations from ft. to ft.	Brown	31 63	
perforations from ft. to ft.	Blue Clay	63 67	
(7) SCREENS: Well screen installed? ☐ Yes ☒ No	Fine Brown Sand	67 71	
Manufacturer's Name	Coarse gravel & Sand	71 97	
Type Model No	Cemented Gravel	97 130	
Diam. Slot size Set from ft. to ft.			
Diam Slot size Set from ft. to ft.			
(8) WELL TESTS: Drawdown is amount water level is lowered below static level			
Was a pump test made? ☐ Yes 🏋 No. If yes, by whom?	, ,		
Yield: gal./min. with ft. drawdown after hrs.			
n · · · · · · · · · · · · · · · · · · ·			
" " "			
COMP. Bailer test 200 gal./min. with 49ft. drawdown after 8 hrs.		- :	
	Work started NOV • 2 1972 Complete	ed Nov. 10 1972	
perature of water 53 Depth artesian flow encountered ft.			
(9) CONSTRUCTION: tine	Date well drilling machine moved off of well	√ov. 10 1972	
Well seal-Material used Cement Grout & Drill Cut-	Drilling Machine Operator's Certification:		
Well sealed from land surface toft.	This well was constructed under my Materials used and information reported	direct supervision.	
Diameter of well bore to bottom of sealin.	best knowledge and belief	above are are to my	
Diameter of well bore below sealin.	[Signed] Ernest Janear	Date Nov. 19,72	
Number of sacks of cement used in well seal sacks	(Drilling Machine Operator)	604	
Number of sacks of bentonite used in well seal sacks	Drilling Machine Operator's License No.		
Brand name of bentonite	Water Well Contractor's Certification:		
Number of pounds of bentonite per 100 gallons	·		
of water lbs./100 gals.	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.		
Was a drive shoe used? 🗌 Yes 📉 No Plugs Size: location ft.	Name Wilcox Drilling & Pu	mp Co.	
Did any strata contain unusable water? Yes No	(Person, firm or corporation) Address P. 0. Box 569, McMi		
Type of water? depth of strata	Address Do		
Method of sealing strata off	[Signed] Janus Hellelow		
Was well gravel packed?X□ Yes □ No Size of gravel: 3/4 Tn.	(Water Well Contractor)		
Gravel placed from 18 ft. to 97 ft.	Contractor's License No. 428 Date	Nov. 10, 19.72	
	The state of the s		