NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

WATER WELL REPORT

WATER RESOURCES DEPARTMENT.
SALEM, OREGON 97310
within 30 days from the date
of well completion.

Gravel placed from

YAMH

STATE OF OREGON

(Please type or print)

"	<i></i>	1,	1 *	rill's
tate	Well No.	501	W-	14ab
		33l		

within 30 days from the date of well completion. (Do not write ab	State Permit No	0		
(1) OWNER:	(10) LOCATION OF WELL:	***************************************		
Name Darrell aylor Address RA L RX 129	County Ya set for // Driller's well number NM/ 34.5 F 34 Section / T.5.5 R. 4 W.M.			
Dayton OR 97/14		7 - 2	.M.	
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivision	on corner .		
New Well ☐ Deepening ☐ Reconditioning ☐ Abandon ☐			—	
If abandonment, describe material and procedure in Item 12.	(11) TYAMED I DYEL CO.	. 11		
(3) TYPE OF WELL: (4) PROPOSED USE (check):	(11) WATER LEVEL: Completed w			
Rotory Driven D	Depth at which water was first found	330	_ <u>ft.</u>	
Jetted Domestic Industrial Municipal	Static level 2.50 ft. below land s	urface. Date 8-8-		
Bored Irrigation Test Well Other	Artesian pressure lbs. per squar	e inch. Date		
(5) CASING INSTALLED: Threaded Welded	(12) WELL LOG: Diameter of well h		11	
6 "Diam from +2 ft. to 78 ft. Gage 1250	, , , , , , , , , , , , , , , , , , ,			
# " Diam. from 0 ft. to 380 ft. Gage/60 PVC.	Depth drilled 380 ft. Depth of comple		ft.	
" Diam. fromft. Gage	Formation: Describe color, texture, grain size and show thickness and nature of each stratum			
	with at least one entry for each change of format	tion. Report each change	e in	
(6) PERFORATIONS: Perforated? Yes No.	position of Static Water Level and indicate prin	cipal water-bearing stra	ata.	
Type of perforator used SaW	MATERIAL	From To SWI	<u>.</u>	
Size of perforations in. by in.	Top Soil	0 2	·	
/00 perforations from 3.60 ft. to 3.00 ft.		***	<u>`</u>	
perforations from ft. to ft.	Brown Clay	2.42		
perforations from ft. to ft.	Weathered Beselt	42 69		
(7) SCREENS: Well screen installed? Yes No	WELLHEREN DESCIT	72 127		
Manufacturer's Name	11 " Hard	69 255		
Type Model No.			_	
Diam Slot size Set from ft. to ft.	Blue Claystone	255279		
Diam Slot size Set from ft. to ft.				
(8) WELL TESTS: Drawdown is amount water level is	Hard Gry Claystone	279 380		
lowered below static level	- SERÉWEI			
a pump test made? Yes - No If yes, by whom?	- NEULIVEL			
Yield: gal./min. with ft. drawdown after hrs.	SEP 1 8 1070		—	
н и н	<u> </u>		—	
a"/r = " from 3"0 "	WATER RESOURCES DE	PT	_	
fler test 2.5 gal./min. with ft. drawdown after 2 hrs.	UALEM, OREGON			
Actesian flow g.p.m.	4 · · · · · · · · · · · · · · · · · · ·			
Temperature of water Depth artesian flow encountered ft.	Work started 8-7 1979Complete	ed 8 - 8 197	<u></u>	
(a) CONSTRUCTION.	Date well drilling machine moved off of well	8-8 19	79	
(9) CONSTRUCTION: Well seal—Material used Ceanen 4 grout		<u> </u>	—	
/ -70	Drilling Machine Operator's Certification: This well was constructed under my	direct supervision	on.	
Well sealed from land surface toft. Diameter of well bore to bottom of sealfin.	Materials used and information reported			
Diameter of well bore below seal	best knowledge and belief.	9-1	79	
Number of sacks of cement used in well seal	[Signed] (Drilling Machine Operator)	Date /, 192	<i>K</i>	
How was cement grout placed? Dumped to	Drilling Machine Operator's License No	/330	×	
be toin of annilos	The state of the s	-		
	Water Well Contractor's Certification:			
	This well was drilled under my jurisdi true to the best of my knowledge and bel		18	
Was a drive shoe used? Yes No Plugs Size: location ft.		uction Inc.		
Did any strata contain unusable water? Yes NO	(Person, firm or corporation)	(Type or print)		
Type of water? depth of strata	Address 868 Delta Dr. N.E. S	saleun	*****	
Method of sealing strata off	[Signed] Nevil Beach			
Was well gravel packed? Yes No Size of gravel:	(Water Well Contr	actor)		

Contractor's License No. ...

696 Date Sept.