

NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report
are to be filed with the

WATER RESOURCES DEPARTMENT,
SALEM, OREGON 97310
within 30 days from the date
of well completion.

WATER WELL REPORT

STATE OF OREGON
(Please type or print)

YAMH

State Well No. 56/4W-17

State Permit No.

(Do not write above this line)

7025

(1) OWNER:

Name Mead Valley Workshop
Address N Hwy 100 Amity Ore

(2) TYPE OF WORK (check):

New Well Deepening Reconditioning Abandon
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary Driven
Cable Jetted
 Bored

(4) PROPOSED USE (check):

Domestic Industrial Municipal
Irrigation Test Well Other

(5) CASING INSTALLED:

Threaded Welded
6" Diam. from 0 ft. to 9.6 ft. Gage 250
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

(6) PERFORATIONS:

Perforated? Yes No. Touch
Type of perforator used
Size of perforations 1/8 in. by 6 in.
80 perforations from 7.0 ft. to 9.0 ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS:

Well screen installed? Yes No
Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level
Comp
Was a pump test made? Yes No If yes, by whom? Driller
Flow: 30 gal./min. with 25 ft. drawdown after 3 hrs.
" " " " "
" " " " "
Baller test gal./min. with ft. drawdown after hrs.
Artesian flow g.p.m.
Temperature of water Depth artesian flow encountered ft.

(9) CONSTRUCTION:

Well seal—Material used Cement grout
Well sealed from land surface to 35 ft.
Diameter of well bore to bottom of seal 11 in.
Diameter of well bore below seal 11 in.
Number of sacks of cement used in well seal 12 sacks
How was cement grout placed? Pumped

Was a drive shoe used? Yes No Plugs Size: location ft.
Did any strata contain unusable water? Yes No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? Yes No Size of gravel: 3/8
Gravel placed from 35 ft. to 9.6 ft.

(10) LOCATION OF WELL:

County Yamhill Driller's well number 681
1/4 1/4 Section 17 T. 55 R. 4W W.M.
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.

Depth at which water was first found 55 ft.
Static level 55 ft. below land surface. Date 2-9-80
Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing 0
Depth drilled 96 ft. Depth of completed well 96 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
Top Soil	0	2	
Brown clay	2	30	
Sticky Brown clay	30	55	
Black sand	55	60	
fine sand	60	70	
Coarse gravel	70	75	
Med gravel with layer of Blue clay	75	90	
S hole	90	96	

RECEIVED
FEB 19 1980
WATER RESOURCES DEPT.
SALEM, OREGON

Work started 2-6 1980 Completed 2-10 1980
Date well drilling machine moved off of well 2-10 1980

Drilling Machine Operator's Certification:
This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] Mike Karasch Date 2-14 1980
(Drilling Machine Operator)
Drilling Machine Operator's License No. 1273

Water Well Contractor's Certification:
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Name BLUE WATER DRILLING CO
(Person, firm or corporation) (Type or print)
Address R1 Box 75 Dayton ORE.
[Signed] Robert S. Helburne
(Water Well Contractor)
Contractor's License No. 417 Date 2-14 1980