

NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

RECEIVED WATER WELL REPORT YAMH JUN 26 1967 STATE OF OREGON (Please type or print) Do not write above this line G-4,21 G-3875

2035 5/4w-18 D State Well No. State Permit No.

(1) OWNER:

Name Marshall Cain Address c/o. 1 Box 213 A. McMinnville, Ore

(2) TYPE OF WORK (check):

New Well [X] Deepening [] Reconditioning [] Abandon [] If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary [X] Cable [] Dug [] Driven [] Jetted [] Bored []

(4) PROPOSED USE (check):

Domestic [] Industrial [] Municipal [] Irrigation [X] Test Well [] Other []

CASING INSTALLED:

10" Diam. from 0 ft. to 84 ft. Gage .250 Threaded [] Welded [X]

PERFORATIONS:

Type of perforator used Torch Perforated? [X] Yes [] No. Size of perforations 1/4 in. by 10 in. 148 perforations from 64 ft. to 84 ft.

(7) SCREENS:

Well screen installed? [] Yes [X] No Manufacturer's Name Type Model No. Diam. Slot size Set from ft. to ft.

(8) WATER LEVEL: Completed well.

Static level 17 ft. below land surface Date May 22/67 Artesian pressure lbs. per square inch Date

(9) WELL TESTS:

Drawdown is amount water level is lowered below static level Was a pump test made? [X] Yes [] No If yes, by whom? Stettler Yield: 230 gal./min. with 67 ft. drawdown after 3 hrs. Baller test gal./min. with ft. drawdown after hrs. Artesian flow g.p.m. Date Temperature of water 54 Was a chemical analysis made? [] Yes [X] No

(10) CONSTRUCTION:

Well seal—Material used Cement Grout Depth of seal 18 ft. Diameter of well bore to bottom of seal 16 in. Were any loose strata cemented off? [] Yes [X] No Depth Was a drive shoe used? [] Yes [X] No Did any strata contain unusable water? [] Yes [X] No Type of water? depth of strata Method of sealing strata off Was well gravel packed? [X] Yes [] No Size of gravel: 3/4 in. Gravel placed from 18 ft. to 84 ft.

(11) LOCATION OF WELL:

County Yamhill Driller's well number NW 1/4 Section 18 T. 550. R. 4W. W.M. Bearing and distance from section or subdivision corner

(12) WELL LOG:

Diameter of well below casing 6 Inch Depth drilled 96 ft. Depth of completed well 84 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level as drilling proceeds. Note drilling rates.

Table with columns: MATERIAL, From, To, SWL. Rows include: Topsoil (0-2), Brown Clay (2-24), Blue Clay (24-63), Sand & Large Gravel (63-84), Brown Cemented Gravel (84-87), Blue Clay (87-96).

Work started May 11 1967 Completed May 22 1967 Date well drilling machine moved off of well May 23 1967

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] James H. Wilcox Date 6-19-67 (Drilling Machine Operator)

Drilling Machine Operator's License No. 172

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

NAME Wilcox Drilling & Pump Co. (Person, firm or corporation) (Type or print)

Address Box 569, McMinnville, Oregon

[Signed] James H. Wilcox (Water Well Contractor)

Contractor's License No. 428 Date 6-19-67 19