YAMH RECEIVED
7279 DEC 02 1980
WATER RESOURCES DEPT
SALEM, OREGON

WATER WELL REPORT
STATE OF OREGON

State Well No. 5S/5W-10

State Permit No.

(1) OWNER:
Name MIKE BUSEMAN
Address RT 3 BOX 68
City McMinnville State OR

(2) TYPE OF WORK (check):
New Well ☑ Deepening ☐ Reconditioning ☐ Abandon ☐
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:
Rotary Air ☑ Driven ☐
Rotary Mud ☐ Dug ☐
Cable ☐ Bored ☐

(4) PROPOSED USE (check):
Domestic ☑ Industrial ☐ Municipal ☐
Irrigation ☐ Test Well ☐ Other ☐
Thermal: Withdrawal ☐ Reinjection ☐

(5) CASING INSTALLED:
Steel ☐ Plastic ☑
Threaded ☐ Welded ☐
6" Diam. from 0 ft. to 40 ft. Gauge 160#
" Diam. from ft. to ft. Gauge

LINER INSTALLED:
4" Diam. from 0 ft. to 110 ft. Gauge 160#

(6) PERFORATIONS:
Perforated? ☑ Yes ☐ No
Type of perforator used SAW
Size of perforations 1/4 in. by 6 in.
50 perforations from 70 ft. to 110 ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS:
Well screen installed? ☐ Yes ☑ No
Manufacturer's Name
Type Model No.
Diam. Slot Size Set from ft. to ft.
Diam. Slot Size Set from ft. to ft.

(8) WELL TESTS:
Drawdown is amount water level is lowered below static level
Was a pump test made? ☐ Yes ☑ No If yes, by whom?
Yield: gal./min. with ft. drawdown after hrs.
" " " "
Air test 50 gal./min. with drill stem at 100 ft. 1 hrs.
Bailer test gal./min. with ft. drawdown after hrs.
Artesian flow g.p.m.
Temperature of water Depth artesian flow encountered ft.

(9) CONSTRUCTION:
Special standards: Yes ☐ No ☑
Well seal—Material used CEMENT GROUT
Well sealed from land surface to 40 ft.
Diameter of well bore to bottom of seal 8-5 in.
Diameter of well bore below seal 6 in.
Number of sacks of cement used in well seal 6 sacks
How was cement grout placed? PUMPED
Was pump installed? Type HP Depth ft.
Was a drive shoe used? ☐ Yes ☑ No Plugs Size: location ft.
Did any strata contain unusable water? ☐ Yes ☑ No
Type of Water? depth of strata
Method of sealing strata off
Was well gravel packed? ☐ Yes ☑ No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:
County Yamhill Driller's well number 735
¼ ¼ Section 10 T. 5S R. 5W W.M.
Tax Lot # Lot Blk Subdivision
Address at well location:

(11) WATER LEVEL: Completed well.
Depth at which water was first found 90 ft.
Static level 35 ft. below land surface. Date 11-22-80
Artesian pressure lbs. per square inch. Date

(12) WELL LOG:
Diameter of well below casing 6
Depth drilled 110 ft. Depth of completed well 110 ft.
Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
TOP SOIL	0	2	
BROWN CLAY	2	30	
BLUE SHALE	30	75	
BROKEN SHALE	75	90	
GRAY SHALE	90	110	

Work started 11-20 1980 Completed 11-22 1980
Date well drilling machine moved off of well 11-22 1980

Drilling Machine Operator's Certification:
This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] Mike Buseman (Drilling Machine Operator) Date 11-25, 1980
Drilling Machine Operator's License No. 1273

Water Well Contractor's Certification:
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Name BLUE WATER DRILLING CO (Person, firm or corporation) (Type or print)
Address RT 1 BX 75 DAYTON, OR
[Signed] Robert D Delbrueno (Water Well Contractor)
Contractor's License No. 417 Date 11-25, 1980

NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the WATER RESOURCES DEPARTMENT, SALEM, OREGON 97310 within 30 days from the date of well completion.

SP*12658-690