NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report
are to be filed with the

WATER RESOURCES DEPARTMENT.
SALEM, OREGON 97310
within 30 days from the date
of well completion.

## WATER WELL REPORT YAMH

## STATE OF OREGON

(Please type or print)
(Do not write above this line)

7280

State Well No. 55/500-10 ba

| (1) OWNER:  | (10) LOCATION OF WELL:   |                                       |
|---|--|---------------------------------------|
| Name Jay Martsolf   | County Yamhill Driller's well number   |                                       |
| Address McMinnville, Ur. 97128  | NE 14 NW 14 Section 10 T. 5S R. 5W W.M.  |                                       |
| (0) MYPPY OF TYOPY (1 1)  | Bearing and distance from section or subdivision corner  |                                       |
| (2) TYPE OF WORK (check):   |  | · · · · · · · · · · · · · · · · · · · |
| New Well Deepening Reconditioning Abandon A   |  |                                       |
| If abandonment, describe material and procedure in Item 12.   | (11) WATER LEVEL: Completed well.  |                                       |
| (3) TYPE OF WELL: (4) PROPOSED USE (check):   | Depth at which water was first found 188 ft.   |                                       |
| Rotary A Driven Domestic L Industrial Municipal Domestic  | Static level 175 ft. below land surface. Date 9/29/80  |                                       |
| □ Bored □ Irrigation □ Test Well □ Other □  | Artesian pressure lbs. per square inch. Date   |                                       |
| (5) CASING INSTALLED: PVC Threaded \( \text{Welded} \( \text{Diam. from} \) 0 ft. to \( \text{18} \) ft. Gage 160PVC            | (12) WELL LOG: Diameter of well below casing 6.  Depth drilled 280 ft. Depth of completed well 280 ft.   |                                       |
| " Diam. fromft. toft. Gage<br>" Diam. from ft. toft. Gage   | Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in   |                                       |
| (6) PERFORATIONS: Perforated? ☐ Yes ☐ No.   | position of Static Water Level and indicate principal water-bearing strata.  |                                       |
| Type of perforator used   | MATERIAL   | From To SWL                           |
| Size of perforations in. by in.   | Topsoil  | 0 1                                   |
| perforations from   | Red Clay<br>Weathered Red & gray basalt  | 8 13                                  |
| perforations fromft. toft   | Coarse Grained Gray Basalt   | 13 280                                |
|   |  |                                       |
| (7) SCREENS: Well screen installed? ☐ Yes ☐ No  |  |                                       |
| Manufacturer's Name   | - Walter State Control of the Contro |                                       |
| Type  |  |                                       |
| Diam.       Slot size       Set from       ft. to       ft.         Diam.       Slot size       Set from       ft. to       ft. |  |                                       |
| Diditi  |  |                                       |
| (8) WELL TESTS: Drawdown is amount water level is lowered below static level  | RECEIVED   |                                       |
| a pump test made?   Yes   No If yes, by whom?   |  |                                       |
| Yield: gal./min. with ft. drawdown after hrs.   | UC   <b>1</b> 5 1980   |                                       |
| n n n n   | WATER RESOURCES DEPT   |                                       |
| Compressor 74 " "   | SALEM, OREGON  |                                       |
| er test 11 gal./min. with 242 ft. drawdown after 4 hrs.   | -  |                                       |
| Artesian flow g.p.m.  |  |                                       |
| Temperature of water 52 Depth artesian flow encountered ft.   | Work started 9/15 180 Completed 9/18 180   |                                       |
| (9) CONSTRUCTION:   | Date well drilling machine moved off of well 9/18 1980   |                                       |
| Well seal—Material used Cement Grout  Well sealed from land surface to 18 ft.   | Drilling Machine Operator's Certification:  This well was constructed under my direct supervision.  Materials used and information reported above are true to my   |                                       |
| Diameter of well bore to bottom of seal   | best knowledge and belief.   |                                       |
| Number of sacks of cement used in well seal   | (Drilling Machine Operator)  Drilling Machine Operator's License No1127  |                                       |
| How was cement grout placed? Hole was clean & dry, grou   | Drining Wachine Operator's Excense No  |                                       |
| introduced from bottom up.  | Water Well Contractor's Certification:   |                                       |
|   | This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.  |                                       |
| Was a drive shoe used? $\square$ Yes $\square$ XNo Plugs Size: location ft.   | · -  |                                       |
| Did any strata contain unusable water?   Yes X No   | Name Wilcox Drilling & Pump Cos (Type or print)  |                                       |
| Type of water? depth of strata  | Address P. O. Box 569, McMin ville, Or. 97128  |                                       |
| Method of sealing strata off  | [Signed Hamls Hills for se   |                                       |
| Was well gravel packed?   Yes   No Size of gravel:  | (Water Well Cont   | ractor)                               |
| Gravel placed from ft. to ft.   | Contractor's License No Date   | , t 19. <sub>0</sub>                  |