NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the STATE OF		55,	16w.	- 28at
	(10) LOCATION OF WELL:			
	County Yamhill Driller's well number			
Name The Delphian Foundation				
Address Rt. 2 Box 195	<u>NE 34 NW 34 Section 28 T. 55 R. 6W W.M.</u>			
Sheridan, Oregon 97878	Bearing and distance from section or subdivision corner			
(2) TYPE OF WORK (check):	Well #2			
New Well Deepening Reconditioning Abandon If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.			
(3) TYPE OF WELL: (4) PROPOSED USE (check):				
Betewer ST Deiron C	Depth at which water was first found 8 ft.			
Cable _ Jetted	Static level 16 ft. below land s	urface.	Date (5-7-75
Dug Image: Bored Image: Image: Image: Bored Image: Image: Image: Bored Image: Image: Bored Image: Bored <thimage: bored<="" th=""> Im</thimage:>	Artesian pressure lbs. per square inch. Date			
CASING INSTALLED: Threaded □ Welded ⊠ 8	(12) WELL LOG: Diameter of well below casing 8 Depth drilled 130 ft. Depth of completed well 130 ft.			
"Diam. from				
	Formation: Describe color, texture, grain size a and show thickness and nature of each stratum			
PERFORATIONS: Perforated? Ves X No.	with at least one entry for each change of forma position of Static Water Level and indicate prin	tion. Rep	ort each	change in
ype of perforator used	MATERIAL	From	То	SWL
	Topsoil-brown	0	1	
	Clay-sandy-w/sandstone	1	<u> </u>	
	boulders-small		5	· · · ·
perforations from ft. to ft.	Clay-brown-sticky	5	8	
perforations from ft. to ft.	Sandstone-blck-hard	8	10	
(7) SCREENS: Well screen installed? Yes X No	Rock-basalt-blck-hard	10	29	
Manufacturer's Name	Rock-basalt-blck-hard	29	58	
Type	Rock-basalt-blck-hard-fract.	58	65	
Diam Slot size Set from ft. to ft.	Rock-basalt-blck-hard-coarse	65		
Diam Slot size Set from ft. to ft.	grain-fract-water		114	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	Rock-basalt-blck-hard	1.14	130	
Aqua				
Was a pump test made? X Yes D No If yes, by whom? Pump Co.		i		
Yield: 41D gal./min. with 977 ft. drawdown after 48hrs.		<u> </u>		
· · · · · · · · · · · · · · · · · · ·				
<i></i>		İ	-	
Bailer test gal./min. with ft. drawdown after hrs.				
Artesian flow g.p.m.	- A-C	<u> </u>		
merature of water Depth artesian flow encountered ft.	Work started 6-3 19 75 Complete	ed	6-7	1975
(9) CONSTRUCTION:	Date well drilling machine moved off of well	A	6_7	1975
Well seal-Material used Pressure Cement Grout	Drilling Machine Operator's Certification:			
Well sealed from land surface to	This well was constructed under my	direct	t supei	vision.
Diameter of well bore to bottom of seal $\frac{12}{12}$ in.	Materials used and information reported best knowledge and belief.	above	are tru	e to my
Diameter of well bore below seal	I The VA AL	Date	6-12	2, 19.75
Number of sacks of cement used in well seal <u>18</u> sacks	(Drilling Machine Operator)			
Number of sacks of bentonite used in well seal	Drilling Machine Operator's License No.	8	.17	••••
Brand name of bentonite				
Number of pounds of bentonite per 100 gallons	Water Well Contractor's Certification:			
of water lbs./100 gals.	This well was drilled under my jurisd		nd this	report is
Was a drive shoe used? [] Yes [2] No Plugs	true to the best of my knowledge and belief.			
Did any strata contain unusable water? 🗌 Yes 📝 No	Name <u>S & M Drilling & Supply</u> , Inc. (Person, firm or corporation) (Type or print)			
	Address 399 SE Walput Street		by. O	
Type of water? depth of strata	11/2 At March	" "		
Method of sealing strata off	[Signed]	actor		
Was well gravel packed? Yes X No Size of gravel:	Contractor's License No			1075
Gravel placed from ft. to ft.	Contractor's Litense No			, 10.1

(USE ADDITIONAL SHEETS IF NECESSARY)

SP*45656-119