NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the STATE ENGINEER, SALEM 10, OREGON within 30 days from the date of well completion.

RECEIVED OCT STATE ENGINEER SALEM, OREGON

WATER WELL REPORT
STATE OF OREGON
(Please type or print)

YAMH 7633

State Well No. 5/6W-34

State Permit No.

(1) OWNER:
Name FRANK H. LUX
Address 804 S.W. MILL
SHERIDAN ORE.

(2) LOCATION OF WELL:
County YAMHILL Driller's well number
¼ ¼ Section T. 5 R. 6 W.M.
Bearing and distance from section or subdivision corner
D.L.C. No. 41
MILES S.W. OF SHERIDAN, ORE

(3) TYPE OF WORK (check):
New Well ☒ Deepening ☐ Reconditioning ☐ Abandon ☐
If abandonment, describe material and procedure in Item 12. GREY

(4) PROPOSED USE (check):
Domestic ☐ Industrial ☐ Municipal ☐
Irrigation ☐ Test Well ☐ Other STOCK

(5) TYPE OF WELL:
Rotary ☐ Driven ☐
Cable ☒ Jetted ☐
Dug ☐ Bored ☐

(6) CASING INSTALLED:
Threaded ☐ Welded ☒
" Diam. from ft. to ft. Gage
6" Diam. from 0 ft. to 20 ft. Gage 2.50
" Diam. from ft. to ft. Gage

(7) PERFORATIONS:
Perforated? ☒ Yes ☐ No
Type of perforator used Cly-oxy
Size of perforations 6 in. by 1/4 in.
perforations from ft. to ft.
Top perforations from 12 ft. to 20 ft.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.

(8) SCREENS:
Well screen installed? ☐ Yes ☒ No
Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(9) CONSTRUCTION:
Well seal—Material used in seal Bentonite Clay
Depth of seal 8 ft. Was a packer used? no
Diameter of well bore to bottom of seal 10 in.
Were any loose strata cemented off? ☐ Yes ☒ No Depth
Was a drive shoe used? ☐ Yes ☒ No
Was well gravel packed? ☐ Yes ☒ No Size of gravel:
Gravel placed from ft. to ft.
Did any strata contain unusable water? ☐ Yes ☐ No
Type of water? Depth of strata
Method of sealing strata off C. Clay.

(10) WATER LEVELS:
Static level 4 ft. below land surface Date 9-27-63
Artesian pressure lbs. per square inch Date

(11) WELL TESTS:
Drawdown is amount water level is lowered below static level
Was a pump test made? ☐ Yes ☒ No If yes, by whom?
Yield: gal./min. with ft. drawdown after hrs.
" " " "
" " " "
Bailer test 3 gal./min. with 20 ft. drawdown after 3 hrs.
Artesian flow g.p.m. Date
Temperature of water 49 Was a chemical analysis made? ☐ Yes ☒ No

(12) WELL LOG:
Diameter of well below casing 6"
Depth drilled 46 ft. Depth of completed well 46 ft.
Formation: *Describe by color, character, size of material and structure, and show thickness of aquifers and the kind and nature of the material in each stratum penetrated, with at least one entry for each change of formation.*

MATERIAL	FROM	TO
TOP SOIL BLACK	0	2
SMALL-BOULDERS-YELLOW CLAY	2	14
POURS-SAND-STONE-WATER-BEA.	14	28
CLAY STONE GREY	28	46

Work started 9-13 1963 Completed 9-27 1963
Date well drilling machine moved off of well 9-28 1963

(13) PUMP:
Manufacturer's Name
Type: H.P.

Water Well Contractor's Certification:
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

NAME KULICK-WEKL DRILLING (Person, firm or corporation) (Type or print)
Address 905-MILL-ST-SHERIDAN, ORE.
Drilling Machine Operator's License No. 78
[Signed] G. L. Kulick (Water Well Contractor)
Contractor's License No. 48 Date 9-27, 1963

(USE ADDITIONAL SHEETS IF NECESSARY)