NOTICE TO WATER WELL CONTRACTOR The original and first copy			· _ ·		
of this report are to be YAMH WAIER WEL	APR 2 4 1975	sala	ω -	31	
STATE OF	OREGON State wen no	1		<u> </u>	
STATE ENGINEER, SALEM, OREGON 97310 978 (Please type within 30 days from the date	CALEN ODECOM State Permit No)		-	
of well completion. (Do not write al	hove this line) LLIN, UNEQUIN	mhil	l –		
			· ·		
(1) OWNER:	(10) LOCATION OF WELL:				
Name John Kroo	County Driller's well nu			<u> </u>	
Address Rt 1 Box 123 A	<u>1/4 1/4 Section 31 т. 2S</u>				
Newberg, Or 97132	Bearing and distance from section or subdivision	on corner	00	<u>A</u>	
(2) TYPE OF WORK (check):					
New Well 👥 Deepening 🗌 Reconditioning 🔲 Abandon 🗌					
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed w	ell.			
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 95 ft.				
Rotary 🗋 Driven 🗋 Domestic 😴 Industrial 🗋 Municipal 🗍	Static level 96 ft. below land surface. Date 4-8 75				
Cable I Jetted Dug Bored Irrigation Test Well Other	Artesian pressure lbs. per squar				
CASING INSTALLED: Threaded Welded	(12) WELL LOG: Diameter of well k	elow casing	<u>, 6</u>	1	
0D" Diam. from 0 ft. to 191 ft. Gage •250	Depth drilled 205 ft. Depth of compl	•	205	ft.	
" Diam. from ft. to ft. Gage	Formation: Describe color, texture, grain size a	and structur	e of m	aterials;	
	and show thickness and nature of each stratum	n and aqui:	fer pen	etrated,	
PERFORATIONS: Perforated? Ves I No.	with at least one entry for each change of formal position of Static Water Level and indicate prin	cipal water-	-bearing	g strata.	
Perforated? Yes No.	MATERIAL	From	то	SWL	
	top soil some boulders	0	3		
size of perforations 1/4 in. by 10 in. 40 perforations from 110 ft. to 190 ft.	soft yellow rock	3	22		
	soft red rock with some hard	22	93		
perforations from ft. to ft.	broken layers				
perforations from ft. to ft.	med soft broken basalt with	93	186		
(7) SCREENS: Well screen installed? 🗆 Yes 🙀 No	some broken layers				
Manufacturer's Name			190		
Type Model No	blue gray sandstone shale	190	205		
Diam Slot size Set from ft. to ft.		↓		<u></u>	
Diam Slot size Set from ft. to ft.	· · · · · · · · · · · · · · · · · · ·	┝──┝─			
(8) WELL TESTS: Drawdown is amount water level is		├			
lowered below static level					
Was a pump test made? 🗋 Yes 🌋 No If yes, by whom?		┼──┼─			
Yield: gal./min. with ft. drawdown after hrs.	- · · · · · · · · · · · · · · · · · · ·				
<u>"</u> " " " "					
<u> </u>					
Bailer test 40 gal./min. with 30 ft. drawdown after 1 hrs.					
Artesian flow g.p.m.					
Temperature of water Depth artesian flow encountered ft.	Work started 4-1- 1975 Complete	ed 4-8		19 75	
	Date well drilling machine moved off of well	4-9		19 75	
CONSTRUCTION:					
Well seal-Material used	Drilling Machine Operator's Certification This well was constructed under my	direct a	super	vision.	
Well sealed from land surface toft.	Materials used and information reported	above ar	e true	to my	
Diameter of well bore to bottom of seal	best knowledge and belief.	Date),7	.75	
Diameter of well bore below seal	(Drilling Machine Operator)				
Number of sacks of cement used in well seal	Duilling Reaching Operator's Liconce No.	50			
Number of sacks of bentonite used in well seal					
Brand name of bentonite Number of pounds of bentonite per 100 gallons	Water Well Contractor's Certification:				
of water lbs./100 gals.	This well was drilled under my jurisd	liction and	this r	eport is	
Was a drive shoe used? X Yes \Box No Plugs Size: location ft.	true to the best of my knowledge and belief. Name JOHN MEEKER WELL DRILLING				
Did any strata contain unusable water? [] Yes X No	(Person, firm or corporation) (Type or print)				
Type of water? depth of strata	Address 2902 Hogver Blad, Newb	erg, Or	971	32	
		n Kr	. /		
Method of sealing strata off	[Signed]		<u> </u>		
	[Signed]	ت (/ 1	19 7 5	